

MPEG-4

NETWORK



Integrated Internal Back Up (UPS)*

Provides a stable stream of power during blackouts, momentary power interruptions & variable voltage incidents for up to **2** hours.
(part# NUB8UP)



Software Screenshot with Clickable Calendar



Independent Channel Adjustment

Independent CH Adjustment & Control
Full Graphical Menu
Easy Calendar Search
Wireless IR Remote Control
New Client Software
Multi Channel Playback

Compression	MPEG4
Display Speed	Real Time for all Channels
Recording Speed	120 Images Per Second
Display Resolution	720 x 480 (D1)
Recording Resolution	360 x 240 (CIF), 720 x 240 (Half D1), 720 x 480 (D1)
Video Inputs	8 CH (Looping Outputs)
Video Output	1 BNC Composite Video / VGA / SVIDEO / SPOT
Audio	4 Inputs / 1 Output
Alarm	8 Inputs / 4 Outputs
PTZ Controls	RS485 Output on Board
Controls	IR Remote Control, USB Plug & Play Mouse
Adjustable Video	Brightness, contrast, color, hue, sharpness
Search Mode	Easy Calendar search, Smart Motion search, Advanced search with preview
Motion Detection	Adjustable motion grid
Storage	3 Internal HDD (Mirroring Raid 1)
Multiplexer Function	(Triplex) Remote view, playback, record, back-up
Menu	Full Interactive GUI (Graphic User Interface)
Back-up	CD/RW and USB output standard
Network	TCP/IP (Remote Access with Client software and IE)
Operation Temperature	41°F~104°F (5°C~40°C)
Power	12 VDC External Transformer (100~240VAC)
Dimensions	432(w) x 406(d) x 89(h) mm

* Optional Feature Sold Separately